

Gravel Buckets

The GB1600 Gravel Bucket has 14 cu. ft. and 1600 lb. capacities. Discharges with positive shutoff to stop flow between loads.

The GB800 Gravel Bucket handles up to 7 cu. ft. and 800 lbs. The bottom discharge has a positive shutoff to stop flow between loads. Its low profile allows greater clearance under the hoist frame.

The GB400 Gravel Bucket has 3-1/2 cu. ft. and 400 lb. capacities. Bottom discharge operates by handles on either side and the trap door is reinforced.

Gravel Bucket Model	GB1600	GB800	GB400
Weight Capacity	1600 lbs.	800 lbs.	400 lbs.
Volume	14 cu. ft.	7 cu. ft.	3-1/2 cu. ft.
Width	30 in.	30 in.	18 in.
Depth	30 in.	30 in.	18 in.
Height	41 in.	29 in.	24 in.
Bottom Opening	10 in. x 10 in	10 in. x 10 in.	---



GB1600
Gravel Bucket
GB400
Gravel Bucket




HF2000
Hoisting
Fork

Hoisting Forks

RGC Hoisting Forks have wheels that make transporting and positioning the forks easy. They are also equipped with pivoting material stops.

Hoisting Fork Model	HF2000	HF1000
Weight Capacity	2000 lbs.	1000 lbs.
Dimensions	38" W x 63" H x 12" D	38" W x 60" H x 35" D
Weight	225 lbs.	163 lbs.



HydraWinch Guard
helps protect operator
from moving parts.

Trash Trays

Trash Tray Model	Large	Small
Weight Capacity	12000 lbs.	400 lbs.
Dimensions	90" W x 40" H x 12" D	61" W x 33" H x 12" D
Weight	165 lbs.	63 lbs.



1200 lb. Trash Tray

Nesting Ballast Weights

Weights are steel encased, have a simple 3-piece snap-lock design and are shipped in knocked down form. When assembled and filled with concrete they weigh 50 lbs. each. Available individually or in 6 and 10 pack sets.



Swing Hoist Hand Winch

Swing Hoist Hand Winches are used to raise HydraPaks to the roof with minimal operator effort.



Available for both the HSI000 and HS2000, they quickly and easily mount to the hoist frames. With 150 ft. of 5/32 in. wire rope they can raise HydraPaks up more than 10 stories.

